# KIP 2300 SCANNER SPECIFICATIONS

KIP 2300 Mono/Colour Scanner

| General	
Scanner Type	C.C.D. with Super-Speed USB3 Technology and KIP RTT Technology
Scan Resolution	600 x 600 dpi optical resolution
Scan Speed	Up to 18 m per minute (Mono), Up to 9 m per minute (Colour)
Scan Formats	TIFF, Multipage TIFF, PDF, PDF-A, Multipage PDF, DWF, Multipage DWF, JPEG, CALS
Scan Destination	Local USB (Removable Media), Unlimited IPS Mailboxes (Local), Unlimited FTP, Unlimited SMB
Original Size Width/Length	Originals Up to 1,066 mm - 914 mm Scan width
Original Thickness	Up to 16 mm Automatic thickness detection
Original Face Up/Face Down	Both - Dual Original Feed Tables
Interface	USB 3.0, Super-Speed USB3 Technology (5 GB per sec data transfer)
Dimensions	1,399 mm W, 480 mm D, 310 mm H
Weight	73 kg
Electrical	100-240V AC 50/60 Hz
Power Consumption	<120 watts

WWW.KIP.COM

KIP 2300 SPACE REQUIREMENTS

KIP 2300 Scanning System Space Requirements

KIP 2300 Side View

KIP 2300 Front View

1600mm

(Rear side)

600mm   KIP2300   600mm

(Front side)   1000mm

(2000mm is required if the document is thicker than 1.2mm)

KIP 2300 Top View

V03/16/18_EU

KIP SCANNER STAND SPECIFICATIONS

839 mm

1,347 mm   686 mm

Width	Height	Length
2,032 mm	839 mm	521 mm

521 mm